

PRIMEQUEST 480 Server

The PRIMEQUEST™ 480 server is your answer to mission-critical capability in the IA arena. With world-leading high availability “System Mirror” hardware technology, Fujitsu supports business critical environments for deploying Microsoft Windows and Linux applications in your data center.

Built within the Fujitsu TRIOLE™ IT optimization strategy of business continuity, agility, and efficiency, PRIMEQUEST is the ideal solution for Microsoft Windows, Linux, 32-bit and 64-bit operations.

The demand for mission-critical IT services is increasing every day. Business requirements dictate that application services and the IT infrastructure that supports them are available all the time, to everyone, everywhere.

However, these availability demands struggle against increasingly rigid cost controls, despite the ever growing desire for rapid business development and new services.

These conflicting demands are best met by the Fujitsu PRIMEQUEST 480 server, where robust mission-critical hardware supports the flexible and cost-effective Microsoft Windows and Linux operating systems, providing an ideal blend of availability, flexibility, and scalability with reduced costs of ownership and operation.

Reliability/Stability/Availability

The Fujitsu PRIMEQUEST 480 server “System Mirror” offers no single point of failure in the crossbars and memory, providing fault immunity for hosted application services. All main components are hot-swappable, and component replacement can be performed without an application halt. Robust hardware isolation of partitions and I/O connections ensure that changes are fully contained within each partition and do not effect other processes.

Flexibility/Scalability

PRIMEQUEST 480 servers allow a combination of scale-up and scale out workloads in the same system frame with multiple system boards and Flexible I/O resources. With up to 32 Intel® Itanium® 2 processors, the PRIMEQUEST 480 server will support your largest applications. The eight partitions and separation of CPU, memory, and I/O, also lets you independently scale resources for multiple applications in a consolidated environment.

Asset Protection/Consolidation/Manageability

The PRIMEQUEST server family is closely aligned with the Intel Itanium Processor (IPF) family, adding new functionality and performance levels as the technology advances. On the software side, the support of Microsoft Windows and Linux standard distributions can maximize the life of your applications. With integrated redundant management processors, your complex consolidated server workload operations and administration are greatly simplified.

Fujitsu is committed to providing its customers with products, solutions and services that will further optimize their IT infrastructure and improve their business agility. Its TRIOLE strategy is the aggregate of three core principles:

- Business continuity (reliability / stability / availability)
- Business agility (flexibility / scalability)
- Business efficiency (asset protection / consolidation / manageability)


Fujitsu has applied these principles to design and deliver the PRIMEQUEST 480 server providing the highest level of availability and performance, now and well into the future.



OVERVIEW

- Processors: Up to 32 (Intel Itanium 2 Processors)
- Crossbar performance: 12.8 GB/sec bidirectional per System Board, 102 GB/sec sustained bandwidth.
- Memory: Maximum of 1 TB
- Partitions: Up to 8 (4 CPU) partitions for mainframe reliability and performance in an open systems server for maximum business continuity, efficiency and flexibility
- Flexible I/O (FIO): Balanced system configuration to optimize application performance

PRIMEQUEST 480 Server



Fujitsu Computer Systems Corporation

Enterprise Sales:

1.800.831.3183
us.fujitsu.com/computers

Consumer Sales (24/7):

1.800.FUJITSU
www.shopfujitsu.com

Fujitsu, and the Fujitsu logo, are registered trademarks and PRIMEQUEST is a trademark or registered trademarks of Fujitsu Limited in Japan and other countries. Intel, the Intel logo, and Intel Itanium, are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. Microsoft, Windows is either a registered trademark or trademark of Microsoft Corp. in the United States and/or other countries. All other trademarks mentioned herein are the property of their respective owners. Product description data represents Fujitsu design objectives and is provided for comparative purposes; actual results may vary based on a variety of factors. Specifications are subject to change without notice.

© 2005 Fujitsu Computer Systems Corporation
All rights reserved. Printed in the U.S.A.
FPC58-1376-03

Type		Floor-Stand
CPU	Processor	Intel® Itanium® 2
	Clock speed	1.6 GHz (9 MB L3 Cache); 1.5 GHz (4 MB L3 Cache)
System	Interconnect	Point-to-point crossbar; Data transfer rate Sustained 102.4 GB/s
	System Board	Max. 8
Main Memory		512 GB (256 x 2 GB); 1TB (256 x 4GB) ²
Hard Disk Drives¹		Max. 4.7 TB (32 x 147 GB Embedded)
Expansion slots¹		Max. 128 (PCI-X) [IOU 8 x 4 + PCI-BOX 8 x 12]
	IOU (8)	64bit/133MHz/Short x16; 64bit/100MHz/Short x16
	PCI-Box	64bit/133MHz/Long x32; 64bit/100MHz/Long x64
Integrated I/O Interfaces	1000Base-T	Max.16 (GSWB required)
	100Base-Tx	6
	External SCSI port	Max. 16
	Video (Analog RGB Dsub 15pin)	1 ⁴
	Serial (Dsub 9pin)	Max. 8 ³
	USB1.1 (KB, Mouse)	4 ⁴
	USB2.0	Max. 16 ³
	UPS (D-Sub 9pin)	2
	DVD-ROM:	1 ⁴
	High reliability	Redundancy
Hot swap		System board, PCI card, Disks, Power unit, Server management processor (MMB), IOU, Gigabit Switch
Partitions		Max. 8
Installation details	Dimension and Weights ⁵	Base Chassis: Width x Depth x Height: 740 x 1,100 x 1800 mm (29.1 x 43.3 x 70.9 inches); Weights: 700kg (1540 lb)
	Power type	AC
	Power Requirements	Voltage: AC200-240V +/-10% Phase mode: Single Phase
	Frequency	50/60Hz +2%,-4%
Other	OS	Red Hat Enterprise Linux AS v.4; Novell SUSE Linux Enterprise Server 9; Microsoft Windows Server 2003, Enterprise Edition for Itanium-Based Systems; Microsoft Windows Server 2003, Datacenter Edition for Itanium-Based Systems
	Other functions	Calendar function (year-month-day-hour-minute-second, Battery Backup function), Automatic Power Control function (Set Power-on, Power-off by day, hour & minute)
	Note1)	Total number in main chassis and optional chassis
	Note2)	Available November, 2005
	Note3)	Required to be installed in each partition
	Note4)	Shared by all partitions
	Note5)	Base cabinet only (not including PCI Box of Extended I/O Cabinet